



Heat Stop Pre-mix



Heat Stop Pre-mix is a ready-to-use product is available in one-gallon (15 lb) or 3.5 gallon (50-lb) pails. Heat Stop Pre-mix works well for firebrick installations in fireplaces, boilers, furnaces and kilns. The color is gray or also available in beige. *This material is water soluble in may only be used with applications that are not exposed to water or moisture.*

PRODUCT DATA

HEAT STOP premix is a ready to use refractory mortar, developed for installation of firebrick in masonry fireplace installations. In addition, this material may also be used in chimneys, boilers, furnaces, kilns and etc.

- Heat Stop Pre-mix is gray in color and shipped in 15 lb. and 50 lb. plastic pails
- For estimating purposes, 50 lbs will lay up approximately 100 firebricks (2 ½ inches thick) if joint thickness is 1/16 inch to 1/8 inch as recommended.
- Mix thoroughly. No other additives required.
- If frozen, unfreeze and mix thoroughly.
- Meets and exceeds ASTM C-199 medium duty.
- Meets all local and national building codes.
- Good for applications well over 2000 OF.
- HEAT STOP premixed is an air setting product, however may be water soluble in service. **Do not use on exterior applications or where excessive moisture may be present.** Use HEAT STOP II Dry Mix non-water soluble products for moisture present applications.

Sandkuhl
clay works